

Aims

- High power-density
- High efficiency
- Durability
- · Low air stoichiometry

R&D activities

- · Durability testing of single cells
- Studies of effects of impurities on electro-chemical performance
- · Adaption of layer design onto improved materials

Equipment

- Electrochemical test facilities
- Permeability measurements
- Coating facilities
- Fuel cell lab



Contacts:

Forschungszentrum Jülich GmbH, D-52425 Jülich, Germany

Institute of Energy and Climate Research IEK-3: Electrochemical Process Engineering

Dr. Martin Müller

Head DMFC

tel +49 (0)2461 61 1859 +49 (0)2461 61 6695 e-mail mar.mueller@fz-juelich.de

Prof. Dr. Detlef Stolten

Director of the IEK-3

+49 (0)2461 61 3076 d.stolten@fz-juelich.de

URL: http://www.fz-juelich.de

http://www.fuelcells.de

Direct Methanol Fuel Cell Systems

Mitglied der Helmholtz-Gemeinschaft

Contact







Power Units for Light Traction and Uninterruptable Power Supply Applications






Direct Methanol Fuel Cells (DMFC)

Electricity generation from methanol

DMFCs directly convert the liquid fuel methanol into electric current. In comparison to other fuel cell systems that operate with pure hydrogen or hydrogen-rich gases from reforming processes, the fuel is supplied directly.

Methanol (Methanol/Water) or Hydrogen

- Methanol
 - Energy density (4,42 KWh/l)
 - Large range without refueling (1,2 kWh/ll)
- Liquid Fuel
 - · Easy refitting
 - + Facy handling
- As biofuel available
 - · Closed CO₂-loop



Direct methanol fuel cells are attractive for various applications, since DMFC systems permit longer operating times due to the high energy density of methanol. Apart that, the DMFC is characterized by easy handling and trouble-free refueling.

Advantages of a DMFC:

- long operation times/large range
- · high energy density of methanol
- · efficient conversion
- fast refuelling
- simple system setup



Aims

- High Power Density
- Durability
- Quality assurance
- Graphite and metallic bipolar plates
- · Safe and durable sealing

R&D activities

- Design and construction of Stacks
- Automated stack assembly
- Advanced operation mode

Equipment

- · Automated durability test facilities
- Robot assisted stack assembly
- Electrochemical test facilities
- Permeability measurements





Aims

- Power Density (> 50 W/l)
- Hybridization
- Durability (> 20,000 h in operation and > 10 years in stand-by)
- System efficiency (>35%)
- Closed water loop up to >40°C ambient temperature

R&D activities

- Durability testing of systems
- Development of water management
- Test of system components
- Development of systems hybridization

Equipment

- Automated durability test facilities
- Climate-testing laboratory
- Air humidification test facility
- FTIR gas analytics
- Two flexible test fields