



JURECA: Cluster Module

General-Purpose Module in Cluster-Booster System



Jülich Research on Exascale Cluster Architectures

- · Successor of the JUROPA system
- Cluster architecture targeting capability and capacity workloads
- · Suitable for compute- and data-intense research
- · Low entrance barrier for new users
- Research vehicle for next-generation cluster architectures
- Project partners: T-Platforms, ParTec

System architecture

- 2.2 Petaflop/s peak performance
 - 45,216 Intel Xeon Haswell cores
 - 150 NVIDIA K80 GPUs
- · 272 TiB main memory
- Based on T-Platforms scalable V-class architecture
- 100 Gb/s Mellanox EDR interconnect with non-blocking full fat tree topology
- 100 GiB+/s storage connection to central IBM Spectrum Scale-based JUST storage cluster
- 20 Tb/s cross-module communication bandwidth to Booster module

Software

- CentOS 7 Enterprise-Linux distribution
- · ParaStation Cluster Management
- Slurm batch system with ParaStation resource management
- · Software Infrastructure shared with Booster module



View of a T-Platforms V-Class V210S dual-socket blade server as used in JURECA.



View of the T-Platforms V5050 chassis. Each chassis can host ten V210S or, alternatively, five GPU-equipped V210F blades.